

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 34; & 3 of T27-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 11 Page 4428)

Set ¼ sec. post, from which
 A B.Oak 6" dia. bears S.75°W., 285 lks. dist.
 A W.Oak 15" dia. bears N.10°E., 96 lks. dist.

H.L. Eppstein, Co. Surveyor - J.H. Wolford; L.L. Singleton;
Feb. 13, 1934 - C.S. File 18/45

Set new corner from 1 old BT.
Drove Star auto axle for corner.
 W.Oak bears N.10°E., 63.6 ft. (Old BT)
 8" Black Walnut bears S.60¼°E. 239.0 ft. mkd. C.S. ¼ S BT

Found OK, J.W.B., 1/27/71 - C.S. File 56/1-9

Bureau of Land Management Dependent Resurvey - Glenn Baughman
under Contract #52500-CT5-1116 - Survey, Oct-Dec. 1975
(DCSO records, Volume 39 Page 15787)

Found - Eppstein's Auto axle firmly set flush with the
 ground.
 An Oak 38" dia. bears N.10°E., 96 lks. dist., with
 healed blaze. (Original BT)
 A Walnut 14" dia. bears S.61°E., 363 lks. dist. with
 healed blaze. (Eppstein BT)

At the corner point, set an iron post 28" long, 2½" dia. 23"
in the ground, with brass cap mkd:

T 26 S R 4 W
 ¼ S 34
 S 3
T 27 S R 4 W
 1975

B.A. Shaner - For: J.A. Barnes - 8/17/81 - C.S. 58/229-40

Found - 2½" I.P with 1975 BLM brass cap.
 38" Oak, orig. BT, with healed face bears N.10°E.,
 63.4 ft.
 14" Walnut with healed face bears S.61°E., 238.6 ft.
 (Record, 239.6 ft.)
 1" iron axle is set alongside brass cap.

continued next page

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 34; & 3 of T27-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 9/26/2000 - C.S. File 66/16-44

Found - 1975 BLM brass cap/iron pipe, protrude 6" above
ground, 1934 axle along south edge of BC/IP
protrudes 4" above ground.
15" now 33" dia., W.Oak with a healed blaze, bears
N.10°E., 64.8 ft. (Rec. N.10°E., 63.4 ft.) (OBT)
8" now 16" dia., B.Walnut with a fully healed blaze
bears S.61°E., 238.6 ft. (1934)
New - 9" dia., W.Oak double blazed & scribed "¼ S4 CS BT"
bears S.62°W., 6.2 ft.
9" dia., W.Oak double blazed & scribed "¼ S34 CS BT"
N.13½°W., 53.0 ft.