

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Secs. 22 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 11 Page 4442)

Set 1/4 sec. post from which
A B.Oak, 15" dia., bears N.45°E., 7 lks.
A B.Oak, 6" dia., bears S.20°E., 54 lks.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 3/19/2002 - C.S. File 66/32-26

Set - 2 3/8" dia., brass cap on a 1 3/8" by 32" long O.D.
iron pipe at proportioned corner position. No BTS
found. BC/IP protrudes 5" out of ground. MKD:
DOUGLAS COUNTY SURVEYORS OFFICE

T 26 S
R 4 W

1/4 S 22
S 27
2002

32" dia., Madrone single blazed & scribed "1/4 S27 CS BT"
bears S.41 1/2°E., 32.1 ft.
17" dia., D.Fir double blazed & scribed "1/4 S27 CS BT"
bears S.65°W., 8.7 ft.
16" dia., D.Fir double blazed & scribed "1/4 S22 CS BT"
bears N.14 3/4°W., 33.4 ft.
Triple trunked madrone double blazed & scribed "1/4 S22
CS BT" on southerly 6" dia. trunk center of root
crown bears N.40 1/2°E., 53.0 ft.
4-way fence corner bears S.21°W., 9.7 ft.
Compass decl. 17 1/2°E.