

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO records, Volume 11 Page 4436)

Set post corner of secs. 26, 27, 22 and 23, from which
A Laurel 2" dia. bears N.56°E., 15 lks. dist.
A Laurel, 2" dia. bears N.35°W., 54 lks. dist.
A B.Oak 14" dia. bears S.2°W., 36 lks. dist.
A B.Oak 5" dia. bears S.27°E., 37 lks. dist.

H.L. Eppstein, Deputy Co. Surveyor - Wit. L.H. Smick; N.E. Richardson;- For: Arthur Blakeley - March 4-5, 1921 - Field Book 54 Page 50 and "Old Cor. renewal book, Page 66".

Set corner from old BT, 5" Oak, in section 26, said Oak was dead but could see old scribe marks. Other trees gone. I renewed corner by setting 4 x 4 x 40" Oak stake. Marked new BTs as follows:
Red Fir 14" dia. bears S.70°30'W., 18 lks. dist.
Red Fir 10" dia. bears N.66°30'W., 35 lks. dist.
Red Fir 12" dia. bears N.32°E., 27 lks. dist.
Red Fir 15" dia. bears S.55°E., 55 lks. dist.

Doug. Co. Surveyors Office - John Powell; F. Jones; J. Brady December 13, 1965 - C.S. File 49/125-102

Found - Found 3/4" iron rod at corner.
12" R.Fir stump N.32°E., 17.8 ft. opened stump, found scribe "B".
14" R.Fir stump S.70½°W., 11.9 ft.
10" R.Fir stump n.66½°W., 23.1 ft.
15" R.Fir stump S.55°E., 36.3 ft.
Set brass cap at sec. cor. mkd: County Surveyors Office, 1965
T26S R4W

S 22	S 23
S 27	S 26

New BTs - 31" Laurel N.88°W., 85.3 ft. scribed T26S R4W S22 CS BT.
30" Fir S.84°E., 196.0 ft. scribed T26S R4W S26 CS BT.
Set iron rod in fence, due North 4.1 ft.

DCSO-GIS Corner visitation - 6/7/2001 - Typed: 1/25/2011 - C.S. File 67/33-1

Monument - BC/IP

Fd. BC by M Schultze, 11/2012 - M164-38A&B