



TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" now 11" dia. W.Oak with a fully healed single blaze, bears N.14 $\frac{3}{4}$ °W., 135.5 ft. (Rec. N.11 $\frac{1}{2}$ °W. 135.5 ft.)  
New BT - A multi-trunk W.Oak double blazed and scribed "1/4 S11 CS BT" on 11" dia. west trunk, bears N.42°E., 114.3 ft. to center of west trunk at base.  
(See condition report in C.S. File 61/6, for additional information).

Found OK by R.Brown - April 1995 - L.P. 1995-0041 A & B  
Fd ok by K. DeGroot, 10/2005 - M148-64

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 1/6/2025 - C.S. File 67/59-38

-----  
Found - DSCO brass cap (Properly MKD)  
40" W.Oak N.52°W. 404.6' blaze rotted out.  
22" W.Oak N.8 $\frac{1}{2}$ °E. 117.0' healed double blaze in N-S fence line.  
17" W.Oak N.14 $\frac{3}{4}$ °W. 135.5' blaze not visible.  
Multi trunk W.Oak scribed 13" trunk N.42°E. 114.3'.  
Note - Barn corner just northerly of fence intersection.  
Fences N.8°E. and S.67°W. Pasture land gentle slope rising to the west.  
Mon on west edge of farm road running northerly.  
Compass decl. 14 $\frac{3}{4}$ °E.  
O CRS COORDINATE SYSTEM  
COTTAGE GROVE-CANYONVILLE ZONE  
N 178309.958 E 213260.145