

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35 of T25-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records, Volume 9 Page 3735)

Set post cor. of secs. 2, 3, 34 and 35, from which
A Laurel 12" dia. bears N.72°W., 17 lks. dist.
A Laurel 10" dia. bears S.79°W., 41 lks. dist.
A Laurel 4" dia. bears S.9°E., 25 lks. dist.
A Fir 20" dia. bears N.55°E., 20 lks. dist.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin
and Roseberry - Special Instructions dated July 8, 1957 and
July 15, 1958 - (DCSO records Volume 29 Page 12261)

The cor. of secs. 2, 3, 34 and 35, determined at record
bearing & dist. from the only remaining orig. BT as follows:

A Fir 45" dia. bears N.55°E., 20 lks. dist., with
scribed marks 35 visible on bark blaze.

At the corner point, set an iron post 28" long 2½" dia. 24"
in the ground, with brass cap marked: T25S R4W

S 34 | S 35
S 3 | S 2
T26S

1957 from which

An Incense Cedar 18" dia. bears N.26½°E., 62 lks. dist.
marked T25S R4W S35 BT.

An I. Cedar 9" dia. bears S.24½°E., 79½ lks. dist. marked
T26S R4W S2 BT.

A Fir 13" dia. bears S.29½°W., 93 lks. dist. marked
T26S R4W S3 BT.

An I. Cedar 25" dia. bears N.47¼°W., 42 lks. dist. marked
T25S R4W S34 BT.