TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & 2 of T27-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 11 Page 4429)

Set ¼ sec. post, from which
A B.Oak 7" dia. bears N.25°E., 68 lks. dist.
A B.Oak 6" dia. bears S.20°W., 80 lks. dist.

Milo E. Godfrey, Doug. Co. Surveyors Office - Wm.Stoffel; Mike Stone - January, 1964 - C.S. File 53/33-63

Found - 18" B.Oak N.25°E., 44.9 ft. This tree opened many years ago, good scribing "BT" visible on badly decayed old face. Tree still alive but top is broken out.
No trace of S.W. bearing tree.
Set brass cap at cor. mkd: County Surveyor's ¼ S 35 T26S R4W
Office, 1964 S 2 T27S
New BTs - 21" B.Oak N.19°W., 43.5 ft. mkd: ¼ S35 CS BT.
27" D.Fir S.25°W., 177.1 ft. mkd: ¼ S 2 CS BT.
3-way fence corner, fences N, S, & E., bears East 2.0 ft.

Corner found and used by:
Bureau of Land Management Dependent Resurvey - Glenn S. Baughman under Contract #52500-CT5-1116 - Survey, Oct/Dec. 1975 (DCSO records, Volume 39 Page 15785-86)