

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 11 Page 4437)

Set ¼ sec. post from which
A Laurel 2" dia. bears S.85°W., 22 lks. dist.
A R.Fir 8" dia. bears N.79°E., 110 lks. dist.

W.H. Wood, Wit: W.S. Crear; O.G. King; A.L. Casebeer
November 1925 - C.S. File 3/20 & Volume 3 pgs. 223-225

Set Iron pipe, Auto spring, for corner, from which
Fir 30" dia. bears N.79°E., 1.10 chs. Old BT.
Fir 8" dia. bears S.25°W., .77 chs. ¼ S 26 BT CS.
Fir 48" N.30°W., 27.5 ft. marked ¼ S 23 CS BT. This
tree was scribed by A. Boyer, Dep. Co. Surveyor
on Dec. 15, 1936. Witnesses were Bert Land and C.F.
Moore. (See C.S. File 16/7)

Douglas Co. Surveyors Office - John Powell - Feb. 1971 - C.S.
File 56/1-1A

Not found. Area logged & very badly burnt. Also possibility
of cat taking BTs & auto spring while clearing for fence line.
Fence line clearing about 30 ft. across.