

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 11 Page 4437)

Set ¼ sec. post, from which
A W.Oak 10" dia. bears N.38½°W., 623 lks. dist.
A B.Oak 27" dia. bears S.33°W., 332 lks. dist.

Don E. Garrett, L.S. #544 - For: Sterchi & Connine
December 1970 - M 40-71

Set brass cap stamped: ¼ Cor. 23/14 T26S, R4W L.S. 544
Scribed BTs:
29" W.Oak bears N.29°W., 409.0 ft. scribed "¼ Sec. 14 BT.
14" W.Oak bears S.31°45'W., 160.2 ft. scribed "¼ Sec. 23
BT."

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 11/30/2000 - C.S. File 66/18-3

Found - 1970 2½" dia., brass cap on a 1½" O.D. IP mkd:
T26S R4W
¼ 14
23 COR
LS 544
W.M. protrudes 8" out of ground.
A 5/8" I.R. is found 0.85 ft. West of BC/IP along
East edge of a North-South fence line.
29" now 36" dia., W.Oak with a fully healed double
blaze, bears N.29°W., 409.9 ft. (1970)
14" W.Oak now cut to ground & rotted, bears
S.31 ¾°W., 160.2 ft. (1970)
New - 18" dia., D.Fir double blazed & scribed "¼ S23 CS
BT" bears S.13°E., 150.8 ft.
NE corner a small shed 24'x36' with conc. floor
bears S.7 ¾°W., 76.3'
NE corner a shop 36'x60' with conc. floor bears
S.77½°W., 62.1'
Dec. 17 ¾°E.

Fd. BC by M Schultze, 11/2012 - M164-38A&B
Fd as per record 6/2020 - by A DeGroot - 2020-0024A&B