

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 2; & 35 of T25-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records, Volume 9 Page 3735-6)

Set ¼ sec. post, from which
 A B.Oak 10" dia. bears N.2°E., 35 lks. dist.
 A Laurel, 6" dia. bears S.21°E., 24 lks. dist.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin
and Roseberry - Special Instructions dated July 8, 1957 and
July 15, 1958 - (DCSO records, Volume 29 Page 12260-61)

Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate
distance, there is no remaining evidence of the orig. corner.
Set an iron post 28" long 2½" dia. 26" in the ground with
brass cap marked: T25S R4W

 ¼ S 35
 S 2
 T26S
 1957 from which
A Fir 10" dia. bears N.60°E., 16 lks. dist. mkd. ¼ S35 BT.
A Fir 12" dia. bears S.49°W., 14½ lks. dist. mkd. ¼ S 2 BT.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy; M. Stone
Aug. 24, 1964 - C.S. File 53/47-22

Found - GLO brass cap set in 1957.
 10" Fir N.60°E., 10.6 ft. is now dead snag, scribing
 visible.
 12" Fir S.49°W., 9.5 ft. uprooted & down, scribing
 visible.
New BTs - 15" D.Fir S.16°E., 21.8 ft. mkd: ¼ S 2 CS BT.
 13" D.Fir N.70°W., 42.2 ft. mkd: ¼ S35 CS BT.
Corner is on point of small spur sloping south; approx. 25 ft.
south of wire fence running E & W; & approx. 75 ft. east of
gate where fence line crosses new logging road.