TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 11 Page 4431)

Set ¼ sec. post, from which
A Laurel 4" dia. bears N.21°E., 38 lks. dist.
A Laurel 8" dia. bears S.68°W., 35 lks. dist.

W.H. Wood; W.S. Crear - Wit: O.G. King; A.L. Casebeer - 11/1925 - C.S. file 3/20; Volume 3 Pgs. 223-225.

Set by proportional measurement. A Fir stake 3" x 3" x 3 ft. ¼ S., from which
A Fir 12" N.26°W., 26 lks. ¼ S. 23 C.S.
Laurel 15" N.80¾°E., 20 lks. ¼ S. 24 C.S.

Co. Surveyors Office - John Powell; W. Penley; J. Heritage Jan. 1971 - C.S. File 56/1-1

Found - 12" D.Fir now stump N.26°W., 17.2 ft. opened for scribe "¼ S".
15" now 15" Laurel N.80¾°E., 13.2 ft. scribe visible 4 S.
Set brass cap at cor. mkd: County Surveyor's T 26 S R 4 W Office 1971 ¼ S 23|S 24
New BTs - 15" D.Fir S.32°E., 48.0 ft. scribed ¼ S24 CS BT.
8" D.Fir S.37°W., 20.8 ft. scribed ¼ S23 CS BT.