



PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 13 & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 4/27/1998 - C.S. File 66/2-17

-----  
Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 12" above ground, properly marked. 1958, Reset as WC in 1964

No OBTs found.

10" now 19" dia., W.Oak, no evidence of blaze visible, bears S.67°W., 169.2' (computed rec. S.66½°W., 168.5'). 1926 - Note: We single blaze low "BT", faces DCSO BC/IP

NE concrete corner of a Quonset hut bears N.84½°W., 239.7' (computed rec. N.83½°W., 239.7') 1958

18" now 24" dia., 4' high W.Oak stump with a fully healed double blaze, bears N.5°E., 34.7' (Agrees w/rec.) 1964

SW BT from 1964 renewal now gone.

NW BT from 1926 renewal now gone.

Set - 5/8" x 32" long iron rod, with DCSO alum. cap at position of corner determined from evidence of past renewals. I.R. set flush with ground.

DCSO BC/IP WC bears East 110.0'. Agrees w/1964 rec.

w/1926 10" NOW 19" W.Oak bears S.34°W., 81.0', agrees rec.

NE cor. concrete Quonset hut, bears N.79¼°W., 131.0' (Rec. N.78°W., 131.0') 1958

New Accessories - From Wit. cor. BC/IP

NE corner of a metal building bears S.54½°W., 73.7' 22" W.Oak, single blazed low "WC BT" faces DCSO BC/IP, bears N.15°W., 68.5'

Note - In near future, new construction may occur. See sketch in file.