

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25 & 36; 30 & 31, T26-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 10 Page 4348-9)

-----  
Set post, cor. to secs. 30, 31, 25, & 36, from which  
A B.Oak, 15" dia., bears S.68°W., 238 lks.  
A B.Oak, 22" dia., bears N.70°W., 291 lks.  
A B.Oak, 15" dia., bears N.58°E., 537 lks.  
No trees convenient SE.

Kris DeGroot - For: Carl Barron - 7/2002 - 2002-0034 A&B

-----  
Found - A Root hole bears N.58°E., 354.42 ft. with an  
uprooted 42" B.Oak alongside with no scribe marks  
visible on a rotted blaze.

Set - 2"x30" iron pipe 26" in the ground with a 3" brass  
cap stamped: T 26 S

R 4 W R 3 W

S 25 | S 30

— S 36 | S 31

2002

PLS 1941

6" D.Fir bears N.42°30'E., 86.2 ft., scribed "T26S  
R3W S30 BT"

6" D.Fir bears S.48°30'E., 21.6 ft., scribed "T26S  
R3W S31 BT"

11" D.Fir bears S.14°15'W., 79.4 ft., scribed "T26S  
R3W S36 BT"

6" D.Fir bears N.22°40'W., 80.9 ft., scribed "T26S  
R4W 25 BT"