

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. 24 & 25; 19 & 30 of T26-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 10 Page 4348)

Set post, cor. to secs. 19, 30, 24 and 25, from which
A B.Oak 20" dia. bears S.10°E., 82 lks. dist.
A B.Oak 25" dia. bears S.54°W., 34 lks. dist.
A B.Oak 18" dia. bears N.61°W., 239 lks. dist.
A B.Oak 23" dia. bears N.78°E., 137 lks. dist.

J.W. Cole, Deputy - Wit: A. Schloeman; S.C. Bruce; Cecil
Black - March/April 1916 - Field Book 41 Page 1; Volume 2
Page 275

I search for evidence of orig. corner and find all witness
trees alive and standing. two of which had been previously
chopped out and I chop out two others, scribe marks plainly
visible on all. I can not make the bearings and distances
called for in original notes coincide, I fulfill as many
calls as possible and set corner which is an Oak Post, also a
1" x 3½' drill steel, from which the original trees bear as
follows:

An Oak 25" dia. bears N.61°W., 134 lks.
An Oak 30" dia. bears S.48°E 80 lks.
An Oak 30" dia. bears N.78°W., 239 lks.
An Oak 30" dia. bears S.54°W., 229 lks.

(See also Field Book 21 Page 9 for Germond Corner)

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; S.A. Bilow
March 19, 1959 - C.S. File 49/48-2

Found - BTs as recorded by Cole, 1916:
30" now 30" down Oak N.61°W., 88.4 ft. I open & find
good scribing "BT".
All other BTs down.
I do not find drill steel at corner.

Set brass cap at sec. cor. mkd: County Surveyors Office 1959
R4W

S 24	S 19
S 25	S 30
T 26 S	

 R3W

New BTs - 16" Laurel bears N.4°W., 223.0 ft. scribed S24 T26S
R4W CS BT.
3" Laurel bears N.42°E., 37.0 ft. scribed CS BT.
12" R.Fir bears S.68°E., 125.8 ft. scribed S30 T26S
R3W CS BT.

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. 24 & 25; 19 & 30 of T26-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Doug. Co. Surveyors Office - Vernon R. Tracy; Mike Stone; Jack Heritage - March 1, 1966 - C.S. File 54/7-50</p> <p>-----</p> <p>Found - 1959 DCS0 brass cap. 16" laurel N.4°W., 223.0 ft. alive & almost healed blaze. 3" Laurel N.42°E., 37.0 ft. blaze healed, alive. 12" R.Fir S.68°E., 125.8 ft. alive, scribe visible on partially healed blaze.</p> <p>New BT - 5" D.Fir S.8°W., 21.4 ft. mkd: S25 CS BT. Corner lies at fence corner, fences N and E. No trace of orig. BT called for in renewal, as area has been cleared and burned.</p>
<p>Found OK in August 1994 by DeGroot - M120-65. Found OK by M. Heimburger, Oct. 2000 - Vol. 20 Pg. 35 A&B Found OK by K. DeGroot, June 2002 - 2002-0034 A & B</p>
<p>Carl Sweeden - For: Gordon Ferguson - 2/2005 - M147-38</p> <p>-----</p> <p>Condition report only</p> <p>Found - Douglas Co. iron pipe & brass cap, up 0.85' (1959) 16' now 23' Madrone BT, scar visible, no tag, dead, N.4°W., 223.0' 3' now 14' Madrone BT, scar visible, no tag, N.42°E., 37.0' 10" Fir stump BT, burned & rotted, face visible, no scribing, S.68°E., 125.8' 5' now 30" D.Fir BT, no scar visible, tag on ground, nails in tree, S.8°W., 21.0'.</p>
<p>Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 3/16/2005 - C.S. File 67/10-14</p> <p>-----</p> <p>Found - 2½" BC on 1¼" OD iron pipe projecting 10" above ground. (properly marked) 5" D.Fir now 31" healed blaze barely visible bears S.11½°W., 21.4 ft. (Rec.S.8°W., 21.4 ft.) 1966 3" Laurel now 14" healed blaze visible bears N.42°E., 37.0 ft. (Agrees w/rec.) 1959 16" Laurel now 23" standing dead, healed blaze visible bears N.4°W., 221.4 ft. (Rec. N.4°W., 223.0 ft.) 1959 12" R.Fir now burnt rotted stump bears S.68°E., 125.8 ft. (Agrees w/rec.) 1959</p> <p>New - 24" D.Fir, double blazed & scribed "T26S R3W S19 CS BT" bears N.89°E., 34.6 ft. cont. next pg</p>

TOWNSHIP 26 RANGE 04 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. 24 & 25; 19 & 30 of T26-3

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

10" B.Oak, double blazed & scribed "T26S R4W S24 CS
BT" bears N.3¼°W., 112.0 ft.
Note - Corner lies at intersection of fences running East-
West & North. Gentle rolling terrain.
Compass decl. 17°E.