

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 039070

PRIMARY CORNER DESCRIPTION SSE Cor. Tyrrell DLC #39

Alias 041010 Description NE Cor Dixon DLC #41
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854

Set Post, from which

A B.Oak 10" dia. bears S.70°W., 163 lks.

A W.Oak 7" dia. bears N.63°W., 80 lks.

G.G. Stewart, DCS - Tom Dixon; Claude Crocker; J.H.Short
Sept. 24, 1922 - C.S. File 1/56

I reset from old BTs. Set iron pipe and mkd. the following trees:

B.Oak 24" dia. bears N.51°E., 52.2 ft.

B.Oak 24" dia. bears S.70°W., 107.6 ft. (old BT)

James W. Byron, Deputy County Surveyor - August-Sept. 1954
C.S. File 46/74 (pg 2)

Found - 1" I.P. at corner.

A 36" B.O. (recorded 24") N.51°E., 52.2 ft. (we find bearing to be N.58°E., 52.2 ft.) chopped out with some scribing visible.

36" B.O. (recorded 24") S.70°W., 107.6 ft. (we find bearing to be S.77°W., 107.6 ft.) original blaze not chopped out and tree dead with center rotted.

Blazed and Scribed:

18" W.Oak S.50°W., 6.0 ft. mkd. N.E. Cl 41 CS BT.

10" W.Oak N.41°W., 28.4 ft. mkd. S.E. Cl 39 CS BT.

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch
- April 12, 2013 - C.S. File 67/38-23

Found - An iron pipe now a 1" ID IP, firmly & plumbly set, protruding 1 ft. above ground and set 1.5 ft. west of a N-S running fence line. 1922

A B.Oak 24" dia., now a root hole with roots and rotted B.Oak fragments nearby; bears S.70°W., 107.6 ft. (as per rec.) Orig.

A W.Oak 7" dia., now a root hole; bears N.63°W., 52.8 ft. (as per rec.) Orig.

A B.Oak 24" dia., now a fallen and out of position rotted out and broken, 24+" dia., B.Oak with no blaze or scribing remaining, the Root hole of which bears N.58°E., 52.2 ft. (as per 1954 rec) 1922

continued next page

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 039070

PRIMARY CORNER DESCRIPTION SSE Cor. Tyrrell DLC #39

Alias 041010 Description NE Cor Dixon DLC #41

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

An 18" W.Oak now a double trunk W.Oak, the scribed trunk of which now is 19" in dia., and shows a fully healed double blaze. A 13" dia., trunk now stands between the scribed trunk and the corner monument. The center of the double trunk bears S.50°W., 5.0 ft. (rec. S.50°W., 6.0 ft. agrees with the base of the scribed trunk) 1954

A 10" W.Oak now a 14" dia., W.Oak with a fully healed double blaze; bears N.41°W., 28.4 ft. (as per rec.) 1954

New - A 12" dia., W.Oak scribed "SSE DLC 39 CS" "BT" on a double blaze; bears N.43°E., 23.0 ft.

A $\frac{5}{8}$ " dia., iron rod firmly and plumbly set protruding 8" above ground (rod is at a fence corner with fences running North-South and West); bears S.5½°E., 24.2 ft.

Note- Monument is on gentle west slope in open oak woodland. Compass decl. 15½°E.