

PRIMARY CORNER DESCRIPTION NE Exterior L cor. for DLC #39

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #28 dated April, 1854  
-----  
Set post, deposited stone 6 x 4. Raised mound with trench as per instructions.

James W. Byron, Deputy Co. Surveyor, September 1954  
C.S. File 46/74 (pgs 38-39) and R.M. 1-14  
-----  
We find no evidence of old corner. Point for corner located by proportional measurement. Set I.P. with brass cap mkd. Cl 39 N.E. Ext. L cor. T26S R5W County Surveyor's Office, 1954.  
Blazed & scribed:  
    14" W.Oak S.1°35'W., 31.7 ft. mkd. N.E. Ex L Cl 39 CS BT  
    18" Pear S.32°15'W., 339.9 ft. mkd. N.E. Ex L Cl 39 CSBT

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch  
- April 15, 2013 - C.S. File 67/38-25  
-----  
Found - No evidence of the orig. monument.  
        A 2½" dia., brass cap (properly marked) on a 1" I.D. iron pipe is firmly set protruding approx. 4" above ground (monument leans slightly south; measurements are to plumb position)  
  
        (All measurements are true and are based on rec. from DCSO Map RM1-14, between NE Int. L and NE Ext. L of DLC 39)  
        A 14" W.Oak, now a double trunk W.Oak the scribed trunk of which is 24" in dia., and shows a fully healed double blaze. The center of the root crown of the double trunk bears S.0¾°W., 31.7 ft. (rec. S.1½°W., 31.7 ft.; bearing is to center of blaze on 24" dia., trunk) 1954  
        An 18" pear, now a double trunk pear the scribed trunk of which is 32" in dia., and shows a partially healed single blaze with illegible scribing. The center of the root crown of the double trunk bears S.32¾°W., 340.8 (rec. S.32¾°W., 339.9 ft.; distance is to scribed face of 32" dia., trunk. 1954  
  
New - Plumb position of fd. BC monument is referenced out and monument is removed from ground (1" dia., IP is fd. to measure 32" long) Bras cap monument is replaced in referenced position and is now approx. 9" below ground surface.

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 039090

PRIMARY CORNER DESCRIPTION NE Exterior L cor for DLC #39

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A  $\frac{5}{8}$ " dia., iron rod protruding 6" above ground, firmly set but with top leaning SE'ly; the plumb position of which bears S.76°E., 97.25 ft. This iron rod is set at corner of fences running North-South and West.

An 11" dia., W.Oak scribed "NE EXT L DLC 39 CS" "BT" on a double blaze; bears S.73 $\frac{3}{4}$ °E., 82.1 ft. A  $\frac{3}{4}$ " dia., 1 ft. long iron bar is embedded horizontally 2 ft. above ground on the north side of the trunk.

A 13" dia., Oregon Ash scribed "NE EXT L DLC 39 CS" "BT" on a double blaze; bears S.77 $\frac{1}{2}$ °W., 131.9 ft.

Note - Monument is in a grass denuded horse pasture on the North side of a shallow westerly running swale. Monument is approx. \_\_\_ ft. from a large and small barn pair.  
Compass decl. 15 $\frac{1}{2}$ °E.