

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 041040

PRIMARY CORNER DESCRIPTION S.E. Cor. Dixon DLC #41

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854

Set post, from which

A B.Oak 10" dia. bears N.42°W., 106 lks.

A W.Oak 10" dia. bears N.63°E., 82 lks.

G. G. Stewart, DCS - Tom Dixon, Claude Crocker, J. H. Short
Sept. 24, 1922 - C.S. File 1/56

I reestablished by running South and East lines of DLC 41.
BTs gone. Set Iron pipe and marked trees as follows:

W.Oak 8" dia. bears N.64°W., 66 ft.

B.Oak 12" dia. bears N.67°E., 62.3 ft.

See 1953 Affidavit in C.S. File 41/144

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike
Stone; Mike Darby; - March & April, 1964; C.S. File 49/125-78

Found - 1" pipe in fence corner. This is a renewal of cor.
set by Woodford, 1953, see notes in C.S. 41/144.
It is not the same location as S.E. corner DLC 41
as set by Stewart, 1922.

New BTs - 8" W.Oak N.57°E., 5.4 ft. mkd. SE DLC 41 CS BT.

10" W.Oak N.25°W., 69.9 ft. mkd. SE DLC 41 CS BT.

Doug. Co. Surveyors Off. V.R.Tracy; L.E. Monrean - March, 1972
C.S. File 49/125-104

Found - 10" W.Oak N.25°W., 69.9 ft. Alive shows good scar.
Tagged.

New road construction has removed other BT and I.P.
at corner.

Set - 5/8" I.Rod in center line of road and set 5/8" I.R.
S.10°W., 29.1 ft. in fence line on R/W for
reference monument.

(Cont. next page)

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 041040

PRIMARY CORNER DESCRIPTION S.E. Cor. Dixon DLC #41

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause
- Oct. 28, 1997 - C.S. 64/78-18

Mon. FD.- PK nail near centerline of paved road.
Bt's FD.- 10" now 16" dia. W.Oak, with a fully healed blaze,
bears N.25°W., 69.9' (agrees with rec.) 1964.
5/8" I.R. in r/w fence line bears S.12½°W., 29.1'
(rec. S.10°W., 29.1') 1972.

New Accessories -

10" Pine not blazed or scribed bears S.48°W.,
84.4' (note pine tree in area).

DCSO Brass cap in a conc. monument "sun 1972"
bears S.33½°E., 812'.

Fd. OK - Oct. 1997 - B. Shaner - M 124-63 & CS 65/15-17

Fd. Ok, Neil Hibbs, Jan. 2006 - M149-25