

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 046010

PRIMARY CORNER DESCRIPTION N.E. Cor. Clinkenbeard DIC #46

Alias 048020 Description NW Cor. Wilbur DIC #48
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854

Set post on line between sections 7 and 18
A W.Oak 12" dia. bears S.5°W., 64 lks.
Raised mound with trench as per instructions.

J.W. Cole, Deputy County Surveyor - May & June, 1921
Volume 3 Page 93

I renewed this corner from the original BT which bears
scribe marks, but is dead. Set at the tree N.5°E., 64 lks.
and set an Oak post also an Iron Bolt 1" x 14" from which:
I marked new trees:
A B.Oak 24" dia. bears S.54°W., 45 ft.
A B.Oak 12" dia. bears S.17°30'E., 72.7 ft.

James W. Byron, Deputy County Surveyor - For McKay
Milo Godfrey; S. Bilow - May 5, 1959 - C.S. File 49/152

Found - 5/8" I.Bolt at corner & both BTs as recorded by
Frear, 1919.
24" now down Oak S.54°W., 45.0 ft. shows good
scribing "46 CS".
12" now 18" B.O. snag S.17½°E., 72.7 ft., center
rotted, no scribing found.
Also find, now 12" Laurel, shows good scribing RP
24 bears S.32°W., 25.0 ft. (not of record)
Set - ¾" I.Rod alongside I.Bolt & scribe new BTs:
12" B.Oak bears N.77°W., 11.8 ft. scribed NE CL 46 CS BT
8" W.Oak bears S.63°W., 22.6 ft. scribed NE CL 46 CS BT.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flauser
May 13, 1997 - C.S. 64/74-31

Mon. Not Found
Bt's FD.- 13" Madrone, with a previously opened blaze,
illegible scribing visible, bears S.32°W., 26'
(1959 rec. S.32°W., 25', dist fits center of
trunk) ?

(Cont. Next Page)

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 046010

PRIMARY CORNER DESCRIPTION N.E. Cor. Clinkenbeard DLC #46

Alias 048020 Description NW Cor. Wilbur DLC #48

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

12" now 16" dia. B.Oak, with a fully healed double blaze, bears N.77°W., 11.8' (agrees with rec. 1959)
8" now 11" dia. W.Oak, with a fully healed double blaze, bears S.63°W., 22.6' (agrees with rec. 1959).
Mon. Set- Chiseled 5" "+" in rock bluff 3" of soil on top of "+".
New Accessories -
20" dia. B.Oak, double blazed and scribed "NW DLC 48 CS BT", bears S.84°E., 70.5' to center of root crown.
Corner lies 9' east of a random fence line