

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 046020

PRIMARY CORNER DESCRIPTION SE Cor. Clinkinbeard DLC #46

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Addison R. Flint, Contract #28 dated April, 1854

Set post, from which
 A B.Oak 12" dia. bears S.75°E., (no dist. given)
 Raised mound with trench as per instructions.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike Stone; Mike Darby - March 1964 - C.S. File 49/125-42

Found - 24" B.Oak S.75°E., 55.7 ft., no dist. given in orig. field notes. Cut open & found good reverse scribing "BT"
 Corner set in N & S fence line running south from SW corner DLC #48
Set - Brass cap at cor. mkd: County Surveyor's office 1964
 T26S R5W S.E. Cor. D.L.C. 46
New BTs - 13" W.Oak N.80°W., 26.7 ft. mkd. S.E. DLC 46 CS BT.
 9" B.Oak N.23°E., 16.2 ft. mkd. SE DLC 46 CS BT.
Note, fence corner, fences North & East bears South 14.0 ft.

Douglas Co. Surveyors Office - Randall Smith; Stephen Flauser August 3, 1988 - C.S. File 62/55-3

Found - DCS0 brass cap, 1964, on a 1½" O.D. I.P. protrudes 8" above ground, properly mkd. BC/IP leans 0.3 ft. West.
 12" now 22" dia. down & rotting Oak with rotted out blaze. No scribing visible. Root hole bears S.75°E., 55.7 ft. (agrees w/rec) Orig. BT.
 13" now 15" dia. W.Oak with a fully healed single blaze bears N.80°W., 26.7 ft. (agrees w/rec)
 9" now 11" dia. B.Oak with a fully healed double blaze bears N.23°E., 16.2 ft. (agrees w/rec.)
No new monument set. 1964 BC/IP returned to plumb position.
New BT - 12" dia. double trunked Madrone, bark scribed "SE DLC 46 CS BT", scribing & dia. are on east trunk, root crown bears S.38½°W., 23.2 ft.
Corner lies 14 ft. North of intersection of an E-W & North running fence lines, in North fence line.

Found OK, July 1993 by Glenn Baughman - M117-34.
Found OK, Dec. 1994 by Donald Bentz - 1995-0016
Found OK, July 1996 by Donald Bentz - 1996-0070