

PRIMARY CORNER DESCRIPTION SW Cor Wilbur DLC 48

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #28 dated April, 1854  
-----  
Set post, from which  
    A B.Oak 30" dia. bears N.12°E., 175 lks.  
    A W.Oak 6" dia. bears N.63°E., 85 lks.

J.W. Cole, Deputy Co. Surveyor, May & June 1921, Vol.3 Pg.93  
-----  
A Rock 6 x 8 x 12" from which A W.Oak 30" dia. bears N.66°30'E., 58.1 ft. This rock had been placed for the corner by some previous surveyor but no record made.

Milo E. Godfrey, Deputy Co. Surveyor; Wm Stoffel; Mike Stone  
February & March 1964, C.S. File 49/125-41  
-----  
Found - Rock called for by Cole.  
    38" W.Oak N.66½°E., 58.1 ft. shows good scar. Did not open.  
    No trace of other tree called for in orig. notes.  
Set - Brass cap alongside Rock & mkd. County Surveyor's Office, 1964 T26S R5W S.W. Cor. DLC 48 |\_\_\_\_\_.  
Blaze & Rescribe: 38" W.Oak N.66½°E., 58.1 ft. mkd. SW DLC 48 CS BT.  
New BTs- 15" W.Oak S.31°E., 67.6 ft. mkd. SW DLC 48 CS BT.  
Note: Corner is in N & S fence line 65 ft. N. of 3-way fence corner, fences North, South and East.

Douglas County Surveyors Office - Randall Smith; Stephen Flause, Linda Rigutto - June 6, 1989 - C.S. File 62/63-18  
-----  
Found - 1964 2½" dia. DCSO B.Cap on a 1¼" O.D. I.Pipe protruding 8" above ground.  
    The center (top) of a 6" x 8" rock protrudes 3" above ground bears South 0.5 ft. from DCSO brass cap. Source unknown.  
(Bearings & distances taken to DCSO BC/IP.)  
    6" now 34" dia. down dead W.Oak with fully healed blazes, root hole bears N.66½°E., 58.1 ft. agrees well with previous renewal records. (possible Orig. BT) We open blazes & find re-scribe marks "SW DLC 48 CS BT" from Godfrey. Old axe marks are found deep in tree near dia. of orig. BT, no blazes or scribing found, these axe marks appear to have been made long ago by someone looking for scribing; center of tree is rotted out.

continued next page

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 048030

PRIMARY CORNER DESCRIPTION SW Cor Wilbur DLC 48

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

15" now 19" dia. W.Oak with a fully healed double blaze, bears S.31°E., 67.6 ft. agrees w/record.  
Orig. 30" dia. b.Oak, NOT FOUND.  
New BTs- 10" dia. W.Oak double blazed & scribed "SW DLC 48 CS BT" bears S.3°E., 22.8 ft.  
19" dia. W.Oak double blazed & scribed "SW DLC 48 CS BT" bears S.58°E., 105.7 ft.

Found OK, July 1993 by Glenn Baughman - M 117-34.  
Found OK, Dec. 1994 by Donald Bentz - 1995-0016  
Found OK, Jan. 1998 by Kristian DeGroot - 1998-0030  
Found OK, April 1999 by K. DeGroot - 1999-0062