

PRIMARY CORNER DESCRIPTION Tps. Cor. (SW Cor. Section 31)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set post cor. to Tps 26 & 27 S. & between Ranges 5 & 6 W.  
from which:

- A Y.Oak, 30" dia. bears N.43°E., 47 lks.
- A W.Oak 12" dia. bears S.68°E., 49 lks.
- A W.Oak 8" dia. bears S.55½°W., 6 lks.
- A W.Oak 13" dia. bears N.43½°W., 86 lk.

-----  
Ben B. Irving - Wit. N.E. Richardson; E. Brown - 1934  
(No source record - See "Old Corner Renewal Volume 1 Pg. 90

-----  
Set from stump, scribe visible, in SE & stump hole in SW.  
Set -1" x 48" pipe 42" in ground with pile of rock 20"  
square base, 12" high, from which  
10" W.Oak bears S.55°W., 27.8 ft. mkd. T27S R6W S1 CSBT.  
6" W.Oak bears S.14°E., 15 ft. mkd. T27S R5W S6 CSBT  
6" W.Oak bears N.73°E., 48 ft. mkd. T26S R5W S31 CS BT.  
10" W.Oak bears N.50°W. 74.1 ft mkd. T26S R6W S36 CSBT

-----  
Found - Oreg. State Hwy. Dept. 1951 - DCSO file G-2

-----  
Douglas Co. Surveyors Office - Gary Langlitz; S.J. Flauser;  
F.C. Silagy - April 24, 1978 - C.S. File 59/46-18

-----  
Fd.- A 1" O.D. I.P. firmly set in a mound of stone.  
We find depressions in the ground & fragments of Oak  
roots at the approx. record position of the orig.  
NE. SE. and NW bearing trees. There is no  
identifiable evidence at these positions.  
A 10" now 13" Fork of a W.Oak alive with well healed  
double blazes bears S.63°W., 27.8 ft. (measured to  
center of root crown at ground level. (Record  
S.55°W., 27.8 ft.)  
6" now 10" W.Oak alive with well healed double blaze  
bears S.14°E., 15.4 ft. (Rec. S.14°E, 15 ft.)  
6" now 9" W.Oak alive with well healed double blaze bears  
N.70°E., 48.0 ft. (Rec. N.73°E., 48 ft.)  
A 10" now 17" W.Oak alive with well healed double blaze  
bears N.48°W., 73.3 ft. (Rec. N.50°W., 74.1 ft.)  
Set- At the location of the found 1" Iron pipe, we set a 1"x  
30" I.P. with brass cap attached 28" in the ground  
surrounded with rock & the found iron pipe  
alongside. Cap mkd. "Douglas Co. Surveyor T26S R6W  
S36 S31 R5W S1 S6.

No new accessories. Found OK, Sept. 20, 1989 - DCSO (File ?)

Cont.

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION Tps. Cor. (SW Cor. Section 31)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. Ok, Bruce Shaner - 4/97 - M 124-45; C.S. 65/13-6B  
Found OK by D.C.S.O. Sept. 2001 - M137-20  
Fd. Ok by R. Quimby, March 2005 - V21 Pgs 56 A&B