

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; & 12 & 13, T26-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set post cor. to secs. 7, 12, 13 and 18, from which  
An Ash 12" dia. bears N.13°W., 355 lks.  
An Ash 12" dia. bears N.28°E., 425 lks.  
Made trench, no other tree near in proper sections.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey S. Bilow  
For: McKay, May 5, 1959 - C.S. File 49/152

-----  
NOTE: This corner is on new 99 highway pavement. It was  
originally a three way fence corner but has been  
used for many years a section corner. Was used &  
referenced out by State Hwy. Dept. before grade was  
built. See C.S. File 49/152 to see sketch as to how  
referenced & points found.

Set- Brass cap at Wit. Cor. for Sec. corner mkd: "Wit. Corner  
120 ft. West to: County Surveyors Office, 1959

S12 | S 7  
S13 | S18

No trees near.

Found OK March, 1986, Carl Schafer - M 100-70

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause  
May 13, 1997 - C.S. 64/74-30

-----  
Found - 2½" dia. Brass cap on a 1½" O.D. iron pipe bent  
southerly of plumb position southerly of plumb  
position 14" unable to read top. This BC/IP  
not dug out as it lies near a fence post and  
beside a ¾" I.R. 1959 BC/IP and ¾" I.R.  
found 18" below ground.

¾" I.R. .3' east (agrees w/rec. M 7-4 1955)  
5/8" I.R. 10" below ground, bears N.6½°E.,  
101.1' (agrees with rec. M 35-45 1968)  
¾" I.R. 8" below ground, bears S.88°22'E.,  
778.1 (rec. S.88°22'E., 277.6' M 7-4 1955)

Set- 2 3/8" dia. Brass cap on a 1 3/8" by 32" long iron  
pipe is set over plumb position of found 1959  
BC/IP. Protrudes 7" above ground.

DOUGLAS COUNTY SURVEYORS

T 26 S

R WIT COR R

6 S12 S07 5

W S13 S18 W

120 FT WEST

1997 OFFICE (Cont. next page)

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7 & 18; and 12 & 13 T26-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Center of a 24" dia. Man hole cover, bears S.61½°E.,  
16.6'.  
10" dia. Columnar shaped poplar, bark scribed "WC  
T26S R5W S7 CS BT", bears N.20°W., 9.8'.  
Corner lies 10" east of easterly r/w fence to I-5

Fd. Ok by D. Bentz - 11/1998 - 1998-116 A & B  
Fd. OK by M. Heimburger, Dec. 1999 - M133-70