

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 7, 18, 17 and 18, from which
A Y.Oak, 12" dia. bears S.74°W., 31 lks.
A Y.Oak, 14" dia. bears N.72°W., 53 lks.
A Laurel, 20" dia. bears N.71½°E., 75 lks.
A Y.Oak, 22" dia. bears S.39½°E., 55 lks.

J.W. Cole, Deputy Co. Surveyor, May & June 1921
Volume 3 Page 93; C.S. File 1/52

Set an Oak stake from which the remains of original BTs
check with field notes. Marked new trees as follows:
A Fir 18" dia. bears S.29°W., 39.2 ft.
A Fir dia. bears N.33°4'E., 36.7 ft.
A Fir 24" dia. bears S.56°10'E., 36.7 ft.
A Fir dia. bears N.59°W., 45.5 ft.

Milo E. Godfrey, Deputy Co. Surveyor; Wm Stoffel; Mike
Stone - Jan & Feb. 1964 - C.S. file 49/125-37

Found - Scribed Oak stake with square iron bar along-side.
21" D.fir S.29°W., 39.2 ft. shows 2 very plain
axe scars.
Fir stump S.56°E., 36.7 ft. shows good scar.
Fir stump N.59°W., 45.5 ft. shows good scar.
Fir stump N.53°E., 30.4 ft. (Not S.33°E., 36.7)
Opened & find good scribing.
Set - Alongside Oak stake, Brass cap mkd. County
Surveyors Office 1964 T26S R5W S7 S8 S17 S17.
New BTs - 7" F.Fir N.23°W., 21.6 ft. mkd. T26S R5W S7 CS BT.
13" D.Fir S.72½°E., 52.9 ft mkd. T26S R5W S17 CS BT
4" D.Fir N.56½°E., 52.4 ft. mkd. S8 CS BT.
Note - A fence corner, fences S & W, bears NE 7 ft.

Fd. BC by M. Schulze, 11/2012 - M164-47