

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set 1/4 Sec. post, from which
 A Y.Oak 18" dia. bears S.50°W., 277 lks.
 A Y.Oak 24" dia. bears S.17¼°E., 285 lks.

Milo E. Godfrey, Deputy - Stoffel; Stone; Darby
March, 1964 - C.S. File 53/51 and RM 1-42

Corner set from survey between section corners and facing of
original BT.

Found - B.Oak, now 38", S.17¼°W (instead of S.17¼°E.) 188.1
ft., opened & found good scribing "S".

Other BT not found.

Set - Brass cap at cor. mkd. County Surveyors Office 1964
T26S R5W ¼ S29|S28

New BTs - 15" B.Oak S.20°W., 13.0 ft. mkd. ¼ S29 CS BT.

12" B.Oak N.34½°E., 19.6 ft. mkd. ¼ S28 CS BT.

Bearings to new trees read with compass set on 19½° East var.

Found OK by D. Edwards, June 2000 - 2000-0034A & B