

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
A W.Oak 16" dia. bears S.1¼°E., 559 lks.
A W.Oak 28" dia. bears N.18°W., 650 lks.

A. Boyer - J.M. Morgan, H.B. Church, Dec. 1, 1944
(no record source) Old "Ren" Vol. 1 Page 69

Reset from original BTs, Set a 1¼" x 30" Iron bar out in a large open hill side. Var. 19°E. from BTs original distances check out fairly close. Both BTs in place, put tags on them.

Milo E. Godfrey, Deputy County Surveyor - Wm. Stoffel; M. Stone; M. Darby - April & May, 1964 - C.S. File 49/125-94

Found - 25" W.Oak S.1¼°E., 368.9 ft. shows good scars.
28" W.Oak N.18°W., 429.0 ft. opened in 1944.
Did not find Iron bar set by Morgan, 1944. (Found yellow tags on both BTs)
Set - Brass cap at cor. mkd. County Surveyor's Office, 1964 T26S R5W ¼ S20|S21
New BTs 15" W.Oak S.41°E., 160.2 ft. mkd. ¼ S21 CS BT.
14" W.Oak S.32°W., 137.5 ft. mkd. ¼ S20 CS BT.
Note - Corner lies in open pasture land approx. 325 ft. east of N. and S. fence line.

Found 1964 County Brass cap. Donald Bentz, Oct. 1991
Survey M 112-37

Found OK by D. Edwards, June 2000 - 2000-0034 A&B