

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set ¼ Sec. post, from which  
    A W.Oak 24" dia. bears N.44°E., 241 lks.  
    A W.Oak 10" dia. bears N.10½°W., 294 lks.

-----  
James W. Byron, Deputy - Milo Godfrey; S.A. Bilow  
December, 1958 - C.S. File 49/128-1

-----  
Found - Orig. 10" now 20" W.Oak N.10½°W., 194.0 ft., I  
        open & find good scribing "¼S".  
        Shell of 30" Oak stump that checks bearing and  
        distance for NE BT., no scribing found.

Set - Brass cap at corner mkd. ¼ S17|S16 T26S R5W  
      County Surveyors Office, 1958.

New BTS - 12" W.Oak bears S.7°E., 59.9 ft. scribed ¼ S16 CSBT  
          12" W.Oak bears N.74°W., 67.6 ft. scribed ¼ S17 CSBT

Note - North-South fence 9 ft. West.