TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post on top of hill, from which
A W.Oak 16" dia. bears N.32°E., 134 lks.
A W.Oak 14" dia. bears S.27°W., 96 lks.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike Stone Mike Darby - March 1964 - C.S. File 49/125-60

Found - 30" W.Oak S.27°W., 63.4 ft. opened & found good reverse scribing "¼S".
No trace of NE bearing tree.
Set - Brass cap at cor. mkd. County Surveyor's Office 1964
T26S R5W ¼ S8|S9
New BTs - 10" B.Oak S.43°W., 36.4 ft. mkd. ¼ S8 CS Bt.
12" B.Oak S.84°E., 27.2 ft. mkd. ¼ S9 CS BT.
Corner lies at south edge of top of E. and W. ridge.

Fd. BC by M. Schulze, 11/2012 - M164-47

Carl Sweeden - For: Tim Clark - Sept. 2016 - M172-33 A&B

Found - 1964 DCSO brass cap up 1.2 and leaning used BTs to set in vertical position prior to tie.
30" now 42" W.Oak BT, S.27°W., 63.4' w/ open face, no scribe vis., no tag.
10" now 18" B.Oak BT, S.43°W., 36.4', scar vis., no tag
12" now 17.5" B.Oak BT, S.84°E., 27.2', scar vis., no tag.

Fd BC by M Heimburger, 1/2019 - M175-18