

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
 A Y.Oak 14" dia. bears S.83½°E., 62 lks.
 A Fir 44" dia. bears S.69°W., 36 lks.

Milo E. Godfrey , Deputy Co. Surveyor - Wm. Stoffel; Mike Stone; Mike Darby - March 1964 - C.S. File 49/125-67

Found - 72" Fir stump S.69°W., 23.8 ft. opened and found reverse scribing, old face at approx. 44" dia. ring count shows correct age.
 No trace of SE BT.
Set - Brass cap at cor. mkd. County Surveyor's Office 1964
 T26S R5S ¼ S 5 | S 4
New BTs - 10" D.Fir N.58°W., 26.0 ft. mkd. ¼ S 5 CS BT.
 12" D.Fir S.10°E., 57.8 ft. mkd. ¼ S 4 CS BT.
3-Way fence corner (fences approx. E-W. and N.) bears S.55°E., 20 ft.

Fd. BC by M. Schulze, 11/2012 - M164-47

Carl Sweeden - For: Tim Clark - Sept. 2016 - M172-33 A&B

Found - 1964 2½" DCSO brass cap up 1.0' w/"T" post along side
 33" D.Fir BT, N.58°W., 26.00', scar, tag, scar faces N.42°E.,
 Remains of 72" dia. D.Fir BT stump, N.69°W., 23.8'
 12" D.Fir BT, S.10°E., 57.8' now gone
Newer wooden fence cor. S.45°E., 23'