

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 & 33

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set ¼ Sec. post, from which  
    A W.Oak 18" dia. bears N.63¾°E., 224 lks.  
    A W.Oak 12" dia. bears S.76°W., 54 lks.

-----  
A. Boyer, DCS - Wit. Geo. Brown; Darley Ware; Gordon Ware  
March 1, 1943 - C.S. File 31/7

-----  
Reset this corner from a rock found for corner & also from  
a W.Oak S.76°W., 54 links. Drove a ½" Iron pin for corner  
beside this rock & scribed a new tree:  
    A W.Oak 12" dia. (Y shaped tree) bears N.23°E., 62.6 ft.  
    scribed the figures and letters "¼ S. B.T." with a  
    knife.

-----  
Douglas Co. Surveyors Office - Milo Godfrey - Mar. 1964 -  
C.S. File 49/125-85

-----  
Fd. Rock - also ½" iron rod set by Boyer in 1943.  
    Also fd. tree mkd. by Boyer, 12" W.Oak N.23°E. 62.6',  
    shows very plain scars. - Good condition.  
Did not renew corner  
A doubt exists in my mind that Boyer actually found orig. cor.  
    Fd. White Oak (approx. 20" dia.,) S.76°W., 35.6' - opened  
    & fd. scribing "RP" - Approx. 50 to 60 yrs. old. - Do not  
    believe this is original BT.  
No trace of either orig. BT. Fd.

-----  
Found OK, S. Ness - August 17, 1992 M 115-59.