

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 4; & 33 of T25-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set 1/4 sec. post, from which

A Fir, 15" dia. bears N.5 1/2°W., 64 lks. dist.

A Dogwood 8" dia. bears S.15°W., 66 lks. dist.

Francis L. Ingram, Deputy Co. Surveyor - John M. Powell -
January 21, 1972 - C.S. File 56/10 and M 44-48

This corner set from resurvey of township line for T25-5
and T26-5

Set - Brass cap at 1/4 cor. mkd. County Surveyors Office

1972 T 25 S R 5 W

1/4 S 33
S 4

T 26 S

New BTs- 15" D.Fir S.70°E., 18.3 ft. scribed 1/4 S4 CS BT.

15" Maple N.11°W., 19.6 ft. scribed 1/4 S33 CS BT.

Daniel Baker - for: Waggoner - 10/05/95 - M 119-74

Set - 1" x 36" Iron pipe with brass cap dated 1994

New - 8" alder, N.86 1/2°W., 34.6' to spike scribed "1/4 S33 BT"

9" ash, N.13°E., 89.5' to spike scribed "1/4 S33 BT"

10" alder, S.66°E., 82.7' to spike scribe "1/4 S4 BT"

7" fir, S.71°W., 100.6' to spike scribed "1/4 S4 BT"

6' aluminum fence post 1' east

Note- Brass cap for 1/4 corner dated 1972, per M44-48, bears
S.7°47'11"W, 152.27' cap removed 10/13/94 per Do.
Co. request.

Carl Sweeden - For: Tim Clark - Sept. 2016 - M172-33 A&B

Found - 1" I.Pipe with 1994 brass cap

8" now 19" alder BT, N.86 1/2°W., 34.6', scar, tag,
nail in bole.

9" now 14" Ash BT, N.13°E., 89.5', double blazed,
scribe vis., tag, nail in bole

10" Alder BT, S.66°E., 82.7', now dead and down, tag

7" now 27" Fir BT, S.71°W., 100.6', double scars,
tag, alum. Post 1.0 E.