

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; & 3, 4 of T27-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----

Set post cor. to Secs. 33, 34, 3 & 4 (in river, course North from which:

- A Y.oak 24" dia. bears N.27½°W., 22 lks.
- A Y.oak 26 dia. bears S.50°W., 75 lks.
- A W.oak 11" dia. bears S.62½°E., 149 lks.
- A W.oak 32" dia. bears N.75°E., 55 lks.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike Stone; Mike Darby - April, 1964 - C.S. File 49/125-92  
-----

Found - 17 W.oak S.62½°E., 98.3 ft. opened & found good scribing "BT", shows good upper scar.  
26" B.oak S.50°W., 49.5 ft. prev. opened & center rotted away.  
Dead & down B.oak N.72½°W., (not N.27½°W) 14.5 ft. prev. opened & center rotted out.

Set - Brass cap at cor. mkd. County Surveyors Office 1964  
T26S S 33 | S 34 R5W  
T27S S 4 | S 3

New BTs - 8" W.oak N.13°W., 25.0 ft. mkd. T26S R5W S33 CS BT.  
6" W.oak N.20°E., 20.5 ft. mkd. S34 CS BT.  
9" W.oak S.58°E., 11.6 ft. mkd. T27S R5W S3 CS BT.  
5" W.oak S.60°W., 18.3 ft. mkd. S4 CS BT.

Corner lies in N. & S. fence line.

Found OK, S. Ness - August 17, 1992 M 115-59.

Found ok by K.DeGroot - 6/1998 - 1998-0071