

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set post cor. to secs. 21, 22, 27 & 28, from which

A Y.Oak 14" dia. bears N.22°E., 39 lks.

A Y.Oak 12" dia. bears S.71°E., 57 lks.

A Y.Oak 7" dia. bears N.26°W., 80 lks.

A W.Oak 14" dia. bears S.55°W., 6 lks.

-----  
Edwin S. Woodford - Wit: M.E. Godfrey - Set on job for  
Worth Davis, August 1952 - C.S. File 42/114-2

-----  
Found 4 old BTs:

14" Y.Oak N.22°E., 39 lks. - standing but dead.

12" Y.Oak S.71°E., 57 lks. - down

7" Y.Oak N.26°W., 80 lks. - found standing

14" W.Oak S.55°W., 6 lks. - standing, but badly rotted.

Set- 2" x 36" iron pipe for corner and mark new trees:

24" W.Oak N.49°E., 36.0 ft. scribe S22 T26S R5W 622 BT.

7" W.Oak S.84°30'E., 39.6 ft. scribe S27 T26S R5W 622 BT.

7" W.Oak S.76°30'W., 2.5 ft. scribe S28 T26S R5W 622 BT.

8" W.Oak N.33°45'W., 32.0 ft. scribe S21 T26S R5W 622 BT.

-----  
Fd. Ok by K. DeGroot Oct. 2003, 2004-0081 A-C