

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract dated April, 1853

Set post, cor. to Secs. 15, 16, 21 and 22, from which
 A W.Oak 14" dia. bears N.59°E., 194 lks.
 A Y.Oak 14" dia. bears S.49¼°E., 204 lks.
 A Y.Oak 13" dia. bears N.13°W., 349 lks.
 A Y.Oak 12" dia. bears S.1½°W., 621 lks.

Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Stone
January, 1964 - C.S. File 49/125-23

Found - W.Oak 24" N.59°E., 128.0 ft. cut open and found good
 reverse scribing "T".
 32" B.Oak S.49½°E., 134.6 ft. shows scars. Did not
 open.
 Rotted remnants of Oak S.1½°W., 410 ft. All reverse
 scribing visible on overgrowth of old scar.
 No trace found of NW BT.
Set - Brass cap at cor. mkd. County Surveyors Office 1964
 T26S R5W S16 | S15
 S21 | S22 Build mound of stones.
New BTs - 12" W.Oak N.11½°W., 77.5 ft. mkd. T26S R5W S16 CS BT
 *9" W.Oak N.5°E., 55.5 ft. mkd: "T26S R5W S16 CS BT
 9" W.Oak S.44°E., 98.7 ft. mkd. T26S R5W S22 CS BT.
 No trees near to SW.
*Added 6/30/2022 per research

Kris DeGroot - For: Rio Nes Partnership - 10/2004 - 2004-0081A-C

Found - No trace of the 1964 DCS0 brass cap & restored this
 corner from the orig. BTs as follows
Set - 1¼"x32" brass capped iron pipe 38" in the ground
 with the 2½" brass cap stamped:
 T26S R5W
 S 16 | S 15
 S 21 | S 22
 2003
 PLS 1941
From which the orig. BTs by Elder & Gile in 1853 in 1853
 A 28" W.Oak bears N.58°48'E, 128.0 ft. with a rotted
 opened face (rec. N.59°E., 194 lks,)
 A 36" burned oak root crown bears S.49°06'E., 134.6
 ft. (Rec. S.49¼°E., 204 lks.)
and a bearing tree by Godfrey, in 1964 per CS 49/125:
 A 20" W.Oak bears S.41°48'E., 99.3 ft. with a healed
 blaze (rec. S.44°E., 98.7 ft)
and new accessories:
continued next page

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 35" W.Oak bears S.81°06'W., 490.8 ft. Scribed
"T26S R5W S21 BT".
Copco power pole 101167 bears N.12°46'W., 415.9 ft
to center of pole with a brass washer stamped
"PLS 1941" nailed into the face of the pole at
0.5 ft. above ground.