

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----

Set ¼ Sec. post, from which  
    A Y.Oak 16" dia. bears S.47½°E., 190 lks.  
    A W.Oak 8" dia. bears S.55°W., 293 lks.  
Var. 17°55' - French's house bears S.59°E.

Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Stone  
January, 1964 - C.S. File 49/125-27  
-----

Found - Rotten Oak stump S.55°W., 193.4 ft. burl wood  
          showing reverse of old axe marks faces cor.  
          Scar is right size, right shape & right  
          position for old BT blaze. I believe it to  
          be overgrowth of old BT blaze. No scribing  
          visible.  
          Stump hole & rotten limbs of Oak on ground fit  
          approx. location of SE BT.  
          Corner location also fits gov't field notes for  
          call at foot of hill.  
Set - Brass cap at cor. mkd. County Surveyors office 1964  
      T26S R5W ¼ S16|S15. Build rock mound.  
New BTs - 18" B.Oak S.6°E., 51.8 ft. mkd. ¼ S15 CS BT.  
          14" W.Oak S.65°E., 11.4 ft. mkd. ¼ S15 CS BT.  
          No trees convenient west of line.