TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
A Y.Oak 8" dia. bears S.10°W., 281 lks.
A Y.Oak 10" dia. bears S.14°E., 220 lks.

Milo E. Godfrey, Deputy Co. Surveyor - Wm.Stoffel; Mike Stone - Feb.& March, 1964 - C.S. File 49/125-39

Found - 16" B.Oak S.10°W., 185.5 ft. Cut open & found good scribing "S".
30" B.Oak S.14°E., 145.2 ft. shows 2 very plain scars. Did not open.
Set - Brass cap at cor. mkd. County Surveyors Office,1964 T26S R5W ¼ S 9|S 10,
New BTs - 12" B.Oak N.41°W., 28.3 ft. mkd. ¼ S9 CS BT.
19" W.Oak N.58°E., 12.2 ft. mkd. ¼ S10 CS BT.
Corner is in draw, approx. 150 ft. N. of small winter creek.

Fd. BC by M. Schulze, 11/2012 - M164-47

Carl Sweeden - For: Tim Clark - Sept. 2016 - M172-33 A&B

Found - 2½" 1964 DCSO brass cap up 0.8'
16" now 22" B. Oak BT, S.10°W., 185.50', no scar no tag
30" B.Oak BT, S.14°E., 145.2' gone 12" now 23" B.Oak BT, N.41°W., 28.30', no scar no tag
19" now 28" W.Oak BT, N.58°E., 12.20', no visible scar no tag.