

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; 33 & 34 of T25-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post, cor. to secs. 3, 4, 33 and 34, from which
A W.Oak 8" dia. bears N.17¼°W., 41 lks. dist.
A W.Oak 12" dia. bears N.25°E., 43 lks. dist.
A W.Oak 16" dia. bears S.75½°E., 218 lks. dist.
A W.Oak 16" dia. bears S.40°W., 26 lks. dist.

Francis L. Ingram, Deputy Co. Surveyor; John M. Powell
C.S. File 56/10 and M 44-48

This corner set from resurvey of township line for T26-5
and T25-5.

Set - Brass cap at cor mkd. County Surveyors T 25 S R 5 W
(Steel fence post alongside) Office S33|S34
S 4|S 3
T 26 S R 5 W

New BTs - 13" B.Oak N.56°W., 42.2 ft. scribed T25S R5W S33
CS BT.
14" D.Fir N.67°E., 60.5 ft. scribed T25S R5W S34
CS BT.
11" W.Oak S.82°E., 49.5 ft. scribed T26S R5W S3 CSBT
15" Maple S.8°W., 46.0 ft. scribed T26S R5W S4 CS BT
East-West fence bears South 45.0 ft.

Fd. Ok by D.Baker, 10/95 - M 119-74

DCSO-GIS Corner visitation - 8/17/2004 - Typed: 1/24/2011 -
C.S. File 67/33-1

Monument - 1.25" BC/IP
Comment - (needs) rehab

Carl Sweeden - For: Tim Clark - Sept. 2016 - M172-33 A&B

Found - 2½" DCSO brass cap 13" B.Oak BT, N.56°W., 42.2',
down and dead, scar, tag
14" D.Fir BT stump, N.67°E., 60.5', rotted, no tag
11" now 20" W.Oak BT, S.82°E., 49.5', tag
15" now 21" Maple BT, S.8°W., 46.0', scar & tag