

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set ¼ Sec. post, from which  
A W.Oak 8" dia. bears S.18¾°E., 234 lks.  
A W.Oak 14" dia. bears N.48°W., 387 lks.

Edwin S. Woodford - Wit: M.E. Godfrey - Set on job for  
Worth Davis, August, 1952 - C.S. File 42/114-3

-----  
Found mound of rock and BTs as follows:  
8" W.Oak S.18¾°E., 234 lks. - original BT.  
14" W.Oak N.48°W., 387 lks. - original BT.  
8" W.Oak S.80½°W., 11.0 ft. scribed R.P.X.  
18" W.Oak N.31¼°E., 24.5 ft. scribed R.P.X.  
8" W.Oak S.5¼°E., 24.5 ft. scribed R.P.X.  
Set a 1" x 30" iron pipe in rock mound.

CONDITION REPORT ONLY

Douglas Co. Surveyors Office - Randall Smith & Stephen Flauser  
- Oct. 29, 1997 - C.S. 64/78-21

-----  
Mon. Fd.- 1" I.D. iron pipe surrounded by a mound of stone,  
protrudes 5" above ground. 1952

Bt's Fd.- 8" now 14" dia. W.Oak, with a previously opened  
partially healed blaze, no scribing visible  
bears S.18 3/4°E., 154.4' (agrees with rec.)  
OBT

14" now 30" dia. W.Oak, with a previously opened  
fully healed blaze, bears N.48°W., 255.4'  
(agrees with rec.) OBT.

8" now 12" dia. W.Oak, with a fully healed single  
blaze, bears S.80½°W., 11.4' (rec. S.80½°W.,  
11', dist. fits blaze) 1952.

18' now 24" dia. W.Oak, with a fully healed single  
blaze, bears N.31¼°E., 25.5' (rec. N.31¼°E.,  
24.5', dist. fits blaze) 1952.

8" now 11" dia. W.Oak, with a fully healed single  
blaze, bears S.5¼°E., 25' (rec. S.5¼°E.,  
24.5', dist. fits blaze) 1952.

Fd. Ok by K. DeGroot Oct. 2003, 2004-0081 A-C