

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 9, 10, 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, contract #31 dated April, 1853

Set post cor. to Secs. 9, 10, 15, 16, from which,
A W.Oak 18" dia. bears N.88°E., 47 lks.
A W.Oak 24" dia. bears S.67½°W., 12 lks.
A W.Oak 6" dia. bears N.80°W., 98 lks.
A Y.Oak 14" dia. bears S.57½°E., 57 lks.

H.E. Crowder, Party Chief for County Engineers Office
April, 1951 - C.S. File 44/47-5

Found original BTs in NE and SW quadrants. From these set
1" x 48" axle 42" in ground to mark sec. cor. From this,
found stump & stump hole corresponding to remaining BTs.
Marked trees as follows:
8" W.Oak N.46°W., 39.5 ft.
24" W.Oak S.63½°W., 14.8 ft.
12" W.Oak S.48°E., 89.0 ft.

Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Stone
January, 1964 - C.S. File 49/125-25

Found - 8" W.Oak now 12" N.46°W., 39.5 ft. opened and
found scribing.
12" W.Oak now 14" S.48°E., 89.0 ft. scribing
visible "T" in not completely healed scar.
Orig. BT, W.Oak now 24" N.88°E., 31.0 ft. is still
standing.
24" W.Oak S.63½°W., 14.8 ft. uprooted & dead, no
other BTs found.
Did not find axle set in 1951.
Set - Brass cap at cor. mkd County Surveyors Office, 1964
T26S R5W S 9 | S 10
S16 | S 15
New BTs - 4" W.Oak north 32.3 ft. mkd. S10 CS BT.
8" W.Oak S.33°W., 35.0 ft. mkd. T26S R5W S16 CS BT.
Corner lies approx. 90 ft SE of centerline Wilbur-Glide Road.

Douglas County Surveyors Off. Randall Smith; S. Flause
February 5, 1986 - C.S. File 62/31-11

Found - A 1964 DCSO brass cap/IP protruding 12" above
ground. (Axle from 1951 not found)
18" now 24" dia. 3½ ft. high stump with a rotted
out center old axe marks & a blaze bears
S.81°E., 32.2 ft. (Rec. N.88°E., 31.0 ft.
dist. possible face measurements) Orig. BT.
No other original BTs found. CONT.

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec Cor for Secs 9, 10, 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" now 16" W.Oak with a fully healed double blaze bears S.48°E., 89.0 ft. (per record)
4" now 6" dia. W.Oak with a fully healed double blaze bears North 32.3 ft. (per record)
New BTs - 14" dia. W.Oak (was thought to be NW BT per 1951, we opened, no scribing was found) single blazed & scribed "T26S R5W S9 CS BT" bears N.43¾°W., 39.9 ft.
4" dia. W.Oak double blazed & scribed "X BT" bears S.21°E., 46.5 ft.
Corner lies in a field approx. 90 ft. SE of North Bank Road centerline & 3½ ft. west of a fence.

Fd. BC by M. Schulze, 11/2012 - M164-47

Carl Sweeden - For: Tim Clark - Sept. 2016 - M172-33 A&B

Found - 2½" 1964 DCSO brass cap up 12"
16" now 19" W.Oak BT, S.48°E., 89.0' healed double blaze with tag
6" now 9" W.Oak BT, north 32.3', with swell no tag
14" now 18" W.Oak BT, N.43¾°W., 39.9', scar vis., tag
4" now 13" W.Oak BT, S.21°E., 46.5' healed blaze, tag

Fd BC by M Heimburger, 1/2019 - M175-18

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - - C.S. File 67/59-40

Found - 2½" 1964 DCSO brass cap (Prop MKD) up 12".
Double trunked 21" W.Oak S.48°E. 89.0' to scribed trunk healed double blazed.
9" W.Oak N.32.3' no blaze visible, add tag.
19" W.Oak N.43¾°W. 39.9' visible scar.
15" W.Oak S.21°E. 46.5' healed blaze.
Note - Compass decl. 14½°E.