

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
 A W.Oak 13" dia. bears N.33½°E., 42 lks.
 A W.Oak 24" dia. bears S.37½°W., 113. lks.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike Stone; Mike Darby - March 1964 - C.S. File 49/125-54

Found - 22" W.Oak N.33½°E., 27.7 ft. (to face). Previously opened, fragments of unmistakable scribing visible on old face.
 32" W.Oak S.37½°W., 74.6 ft. (to face), shows good scar. Did not open.
Set - Brass cap at cor. mkd. County Surveyors Office 1964
 T26S R5W ¼ S3 S 10
New BTs - 12" W.Oak S.8°E., 18.2 ft. mkd. ¼ S10 CS BT.
 14" D.Fir N.9°E., 50.4 ft. mkd. ¼ S3 CS BT.
Corner lies approx. 50 ft. south of small creek. (Winter)

BLM Dependent resurvey by Timothy J. Moore, A. Bert Skeesick, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2065 surveyed May 2004/April 2005 - (DCSO records Vol. 57 Page(s) 22459)

The ¼ sec. cor. of secs. 3 & 10, perpetuated by Godfrey, in 1964, monumented with an iron pipe, 1½" dia., loosely set, projecting 20" above the ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T26S 1/4 S3 S10 R5W 1964 from which the remains of an original bearing tree
 A roothole bears N.33½°E., 27.7 ft., alongside of which is the oak trunk, 19" dia., with no marks visible on an opened decayed blaze.
and the bearing trees mkd. by Godfrey
 A fir, 18" dia., bears N.9°E., 50.4 ft., with a healed double blaze.
 An oak, 21" dia., bears S.6°E., 18.1 ft., with a healed double blaze.

At the corner point
Remove the loosely set iron pipe, and in its place, set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd.
 T26S R5W
 ¼ S 3
 S 10
 2004

Deposit a magnet in a white plastic case at the base of the stainless steel post, and bury the iron pipe along S. side of stainless steel post.