

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 for Secs. 34 and 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----

Set ¼ Sec. post, from which  
    A W.Oak 18" dia. bears N.7°W., 374 lks.  
    A W.Oak 20" dia. bears N.6°E., 359 lks.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike Stone; Mike Darby - April, 1964 - C.S. file 49/125-82  
-----

Found - Old rotted Oak stump N.7°W., 246.8 ft. opened and found good scribing.  
          Rotted Oak stump N.6°E., 236.9 ft. no marks found.  
Set - Brass cap at cor. mkd. County Surveyors Office, 1964  
          T26S R5W ¼ S34|S35.  
New BTs - 14" W.Oak N.12°W., 168.0 ft. mkd. ¼ S34 CS BT.  
          8" W.Oak N.28°E., 171.0 ft. mkd. ¼ S35 CS BT.  
Corner lies in open, grassy, nearly level pasture land, approx. 240 ft. south of small winter creek.