

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 14, 15, 22 & 23, from which

- A Y.Oak 15" dia. bears N.83½°W., 425 lks.
- A W.Oak 10" dia. bears S.87½°W., 510 lks.
- A W.Oak 14" dia. bears N.78½°E., 670 lks.
- A W.Oak 11" dia. bears S.48¾°E., 472 lks.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; S.A. Bilow; - December, 1958 - C.S. File 49/128-8

Found - Orig. 14" now 24" W.Oak N.78½°E., 442.2 ft. I open & find good scribing "S".
Orig. 15" now 40" B.Oak N.83½°W., 280.5 ft. I do not open.
Orig. 11" now 20" W.Oak S.48¾°E., 311.5 ft. I open & find good scribing "S23".
Original SW BT not found.

I locate position of section corner by distance intersected bearings are about 2° in error.

Set - Brass cap at corner mkd.

S 15	S 14	T26S R5W
S 22	S 23	

County Surveyors Office, 1958.

New BTs - 13" W.Oak bears S.27°E., 167.0 ft. scribed S23 T26S R.5W CS BT.
12" W.Oak bears N.77°E., 373.4 ft. scribed S14 T26S R5W CS BT.
20" W.Oak bears N.80°W., 158.3 ft. scribed S15 T26S R5W CS BT.
No trees near to S.W.

Douglas County Surveyor's Office; Randall Smith, Stephen Flause, Oct. 28, 1997 - C.S. File 64/78-16 Cond. report only

Monument Found - 2½" Brass cap dated 1958 on a 1½" O.D. iron pipe, protrudes 15" above ground.

Accessories Found -

Note - Orig. bearings in 1958 renewal noted as having a 2° rotation.

14" now 33" dia. W.Oak with a previously opened partially healed blaze, no scribing visible, bears N.80½°E., 440.4 ft. (orig. rec. N.78½°E., 442.2 ft. Dist fits well for a slope measurement). OBT
(Cont. next page)

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

15" now 40" down and rotted Oak, old blaze and illegible scribing found (orig. rec. N.83½°W., 280.5 ft.) OBT

11" now 28" dia. W.Oak with a previously opened partially healed blaze, no scribing visible, bears S.46 3/4°E., 311.5 ft. (orig. rec. S.48 3/4°E., 311.5 ft.) OBT

13" now 19" dia. W.Oak with a fully healed double blaze, bears S.27°E., 166.4 ft. (rec. S.27°E., 167.0 ft.) 1958

12" now 17" dia. W.Oak with a fully healed double blaze, bears N.77°E., 372.9 ft. (rec. N.77°E., 373.4 ft.) 1958

20" now 25" dia. W.Oak with a fully healed double blaze, bears N.80°W., 158.3 ft. (agrees with rec.)

Note - Surrounded monument with a mound of stone.

Fd. Ok by K. DeGroot, 10/2003 - 2004-0081 A-C