

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>Original - Elder &amp; Gile, Contract #31 dated April, 1853 ----- Set ¼ Sec. post, from which     A Pine 36" dia. bears N.35°E., 43 lks.     A Y.Oak 9" dia. bears S.88½°W., 73 lks.</p>
<p>James W. Byron, Deputy - Milo Godfrey; S.A. Bilow - December, 1958 - C.S. File 49/128-5 ----- Found - Orig. 36" now 48" Pine, partly rotted snag, N.35°E 28.4 ft. I find section of old face showing good axe marks &amp; scribing "S"         No trace of original SW BT. Set - Brass cap at corner mkd. County Surveyor's Office 1958, ¼ S15 S14 T26S R5W New BTs - 16" R.Fir bears S.61°W., 18.7 ft. scribed S15 ¼ CSBT           18" R.Fir bears S.32½°E. 25.6 ft. scribed ¼ S14 CSBT</p>
<p>Douglas Co. Surveyors Office - Randall Smith &amp; Stephen Flause - Oct. 29, 1997 - C.S. 64/78-19 ----- Found - 2½" dia. brass cap on a 1½" OD iron pipe protrudes 10" above ground. 1958         36" pine now large root hole, agrees with rec. N.35°E., 28.4'. 0BT         18" now 23" dia. D.Fir, with a fully healed double blaze, bears S.32½°E., 25.6' (agrees with rec.) 1958         16" now 14" dia. 4' high D.Fir snag, with a healed lower blaze scribing found in upper blaze "¼ S15 CS", bears S.61°W., 18.7' (agrees with rec.) 1958 New - 10" dia. W.Oak, double blazed and scribed "¼ S 15 CS BT", bears S.45½°W., 98.1'.       6" dia. Madrone bark scribed "¼ S15 CS BT", bears S.5½°W., 15.9'.       11" dia. W.Oak, double blazed and scribed "¼ S14 CS BT", bears N.0½°E., 102.4'.</p>
<p>Fd. Ok by K. DeGroot, 10/2003 - 2004-0081 A-C</p>
<p> </p>