

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 500511

PRIMARY CORNER DESCRIPTION M.C. right bank bet secs 10 & 11

Alias 855480 Description Meander Corner
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set Meander post on right bank, from which
 A W.Oak 10" dia. bears N.25½°W., 207 lks.
 A W.Oak 13" dia. bears N.16°E., 291 lks.
Current in river rapid. Banks low and gravelly.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; S.A.
Bilow - December, 1958 - C.S. File 49/128-9

Found - Orig. 10" now 24" W.Oak N.25½°W., 136.6 ft. I open
 and find good scribing "BT S10".
 Orig. 13" now 29" W.Oak N.16°E., 192.1 ft. Shows
 good scar, I do not open.

Note - Corner in River. SET WITNESS CORNER.

Set - Brass cap at wit. cor. mkd: Wit. Cor. 185 ft. south
 to M.C. S10|S11, T26S R5W County Surveyors
 Office, 1958.

New BTs - 29" W.Oak (orig. NE BT for M.C.) East 53.5 ft.
 scribed WC MC S11 CS BT.
 7" W.Oak bears S.62°W., 3.8 ft. scribed WC MC
 S10 CS BT.