

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
 A Y.Oak 18" dia. bears N.57°E., 625 lks.
 A Y.Oak 20" dia. bears N.1°W., 691 lks.

James W. Byron, Deputy County Surveyor - Milo Godfrey;
S.A. Bilow - December, 1958 - C.S. 49/128-9

Found - Orig. 20" now 48" B.Oak N.1°W., 456.1 ft. I open &
 find good scribing "BT".
 No trace of original N.E. BT.
Set - Brass cap at corner mkd: ¼ S10|S11 T26S R5W County
 Surveyors Office, 1958.
New BTs - 6" W.Oak bears N.74°W., 24.4 ft. scribed ¼ S10 CSBT
 13" B.Oak bears S.8°E., 33.2 ft. scribed ¼ S11 CSBT

BLM Dependent resurvey by Timothy J. Moore, A. Bert Skeesick,
Cadastral Surveyors and Robert H. Browning, Survey Tech,
under Group No. 2065 surveyed May 2004/April 2005 - (DCSO
records Vol. 57 Page(s) 22454)

The ¼ sec cor of secs. 10 & 11, perpetuated by Byron, in 1958
monumented with an iron post, 1¼" dia. firmly set, projecting
12" above the ground, with brass cap (properly) mkd.
from which the remains of an original bearing tree
 A roothole bears N.3°W., 457.5 ft., alongside of which
 is the oak trunk, 50" dia., with no marks visible
 on an opened blaze. (Record, N.1°W., 456.1 ft.)
and the bearing trees mkd. by Byron
 An oak, 20" dia., bears S.9¼°E., 36.0 ft., with a healed
 double blaze.
 An oak, 14" dia., bears N.74¼°W., 24.7 ft., with a
 healed double blaze.

Corner is located 4.1 ft. N. of the cor. of fences, woven
wire fences, extending south and east.

The geographic position (NAD 1983 (CORS 96)) of the ¼ section
corner of sections 10 & 11, as determined from a tie to
geodetic control station EC 41298, established by the BLM in
2004, (see the Control Data Sheet attached to these field
notes following the General Description), is as follows:
Latitude: 43°19'25.23"N Longitude: 123°15'58.93"W