TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853 - (DCSO records Vol. 11 Page 4492)

Set ¼ Sec. Post, from which
A Y.Oak 22" dia., bears S.64°W., 134 lks.
A Y.Oak 10" dia., bears S.11½°E., 185 lks.

Douglas Co. Surveyors Office - Milo Godfrey - Mar. 1964 - C.S. File 49/125-42(pg2)

Not found.

BLM Dependent resurvey by Timothy J. Moore, A. Bert Skeesick, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2065 surveyed May 2004/April 2005 - (DCSO records Vol. 57 Page(s) 22457-8)

Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate dist., there is no remaining evidence of the original cor. Drive a finned aluminum rod, 36" long, 3/4" dia., 36" in the ground, with aluminum cap mkd. T26S R5W

¼
S 3|S 2
2004

from which
An oak, 18" dia., bears N.47¼°E., 278.7 ft mkd. ¼ S2 BT
A maple, 8" dia., bears S.74¾°W., 84.4 ft., mkd. ¼ S3 BT
Deposit a magnet in a white plastic case alongside of the finned aluminum rod.