

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 534500

PRIMARY CORNER DESCRIPTION WC MC W bank N. Um. river, secs 11 & 14

Alias <u>856340</u>	Description <u>M.C.</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set Meander post on left bank river, from which

A Y.Oak 24" dia. bears N.41½°W., 346 lks.

A Y.Oak 20" dia. bears S.52¾°W., 443 lks.

Course of river N.20°E., Bank 10 feet high.

James W. Byron, Deputy County Surveyor - September 1954
C.S. File 46/74 (pgs 32-33) and R.M. 1-14

We found both original BTs and used record distances to fix position of Meander Corner. The Northwest BT is down and rotten - we cut out old blaze & found old scribing in fair condition. The Southwest BT is a standing snag. We cut out old blaze & found scribing in good condition.

Set - A 1" I.P. with brass cap for Witness corner 100 ft. west of Meander cor. and mkd. W.C. 100' W. M.C. 11 T26S
R5W County Surveyors Office, 1954. 14

Blazed and scribed:
14" W.Oak N.0°56'30"E., 30.0 ft. mkd. W.C. S14 CS BT.
14" W.Oak S.65°46'30"W., 14.3 ft. mkd. W.C. S14 CS BT.

Fd BC & 2 BTs, good condition DCS0 MG 4/1/1964 C.S.49/125-72