

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 35; & S. 2, T27-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----

Set ¼ Sec. post, from which  
A Y.Oak, 24" dia. bears N.48°W., 132 lks. dist.  
A W.Oak, 18" dia. bears S.81°W., 487 lks. dist.

Milo E. Godfrey & Crew - March 31, 1964 - C.S. 49/125-100  
-----

Found - Stump of W.Oak, S.81°W., 321.4 ft., now 24", opened  
& fd. good scribing.  
48" B.Oak, N.48°W., 87.1 ft. Faint scar visible.  
Did not open.  
Set - Brass cap at cor. mkd. County Surveyors T26S ¼ S35  
Office, 1964 T27S S 2  
R5W  
New BTs - 9" W.Oak, S.20°W., 58.0 ft. mkd. ¼ S2 CS BT.  
12" W.Oak, N.79°W., 85.6 ft. mkd. ¼ S35 CS BT.  
Note - Bearings not true for this corner, read with compass  
set for Var. 19° 30' E.

Douglas County Surveyors Office - Randall Smith & Stephen  
Flause - 6/22/94 - CS 64/52-4  
-----

Found - 2½" Brass cap on 1½" O.D. Iron Pipe protruding 16"  
above ground (1964) COUNTY SURVEYORS OFFICE  
T 26 S  
¼ S 35 R  
S 2 5  
T 27 S W  
1964  
BTs - Orig SW BT Now Gone  
24" Now 48" dia., B. Oak with a possible scar, bears  
N.61°W. 87.1' (rec. N.48°W. 87.1') OBT  
9" now 14" dia., W. Oak with a fully healed double  
blaze, bears S.20°W. 58' (agrees with rec) 1964  
12" now 13" dia., W. Oak with a fully haled double  
blaze, bears N.79°W. 85.6' (agrees with rec)  
New Accessories -  
17" dia., W. Oak double blazed and scribed "¼S2 CS  
BT", bears S.5°W. 104.7'.