

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Corner Secs 23 and 26

Alias 855220 Description Meander Corner on high bank
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
 A W.Oak 8" dia. bears N.74¼°E., 1060 lks.
 A W.Oak 24" dia. bears S.71½°W., 346 lks.
This post is also a Meander corner on high bank.

Milo E. Godfrey, Deputy - Wm. Stoffel; Mike Stone
January & February, 1964 - C.S. File 49/125-34

Found - 21" W.Oak N.76¼°E., 699.6 ft. Cut open & found
 good scribing "¼S".
 Slight depression in ground (possible old stump
 hole) S.71½°W., 228.4 ft.
Set - Brass cap at cor. mkd. County Surveyors Office 1964
 T26S R5W ¼ S23 S26.
New BTs - 14" triple W.Oak (measured below forks) N.68°W.,
 123.4 ft. mkd. ¼ S23 CS BT.
 18" W.Oak S.87½°W., 182.9 ft. mkd. ¼ S26 CS BT.
Note - The iron rod at south corner of Lots 7 & 8, "Echo
 Bend" bears S.82½°W., 140.2 ft.
 The iron rod at the south corner of Lots 6 & 7,
 "Echo Bend" bears S.7½°W., 46.8 ft.

Douglas County Surveyors Office - Randall Smith, Stephen J.
Flause - Feb. 27, 1986 - C.S. File 62/34-3

Found - 1964 DCSO brass cap/iron pipe 6" below ground.
 Orig. BT 8" now 23" dia. W.Oak with a previously
 opened blaze scribe visible "¼S" bearings &
 distances not checked (Rec. N.76¼°E., 699.6 ft
 Original SW BT not found.
 14" now 19" dia. triple trunked W.Oak (dia. taken
 on scribed south trunk) with a fully healed
 double blaze bears N.66°W., 123.4 ft. (Rec.
 N.68°W.)
 18" now 23" dia. W.Oak with a fully healed double
 blaze bears S.87½°W., 182.9 ft. (agrees w/rec)
 ¾" I.R. at south cor. of Lots 7 & 8, Echo Bend
 Subd. bears S.82½°W., 140.2 ft. (agrees w/rec)
 ¾" I.R. at south cor. Lots 6 & 7 "Echo Bend Subd"
 bears S.7½°W., 46.8 ft. (agrees w/rec.)
New - NW cor. of concrete foundation of house bears
 S.35¼°E., 10.6 ft.