

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853 -
(DCSO records Vol. 11 Page 4491)

Set ¼ Sec. Post, from which
 A Y.Oak 10" dia., bears S.34°E., 66 lks.
 A Y.Oak 15" dia., bears N.40°W., 95 lks.

G. R. Lecklider - For: Bernard Grubbe - 9/1961 (added
9/12/2011) - M21-29

Set by prop. meas. for departure only. Did not run control
to establish ¼ cor. for latitude.

Set: "T" bar in solid rock
 6" W.Oak - S.45°E., 32.1' mkd. "A 1, BT"
 6" W.Oak - West - 26.0' mkd. "A 2, BT"

Douglas Co. Surveyors Office - Milo Godfrey - Feb. 1964 -
C.S. File 49/125-28

Not found.

BLM Dependent resurvey by Timothy J. Moore, A. Bert Skeesick,
Cadastral Surveyors and Robert H. Browning, Survey Tech,
under Group No. 2065 surveyed May 2004/April 2005 - (DCSO
records Vol. 57 Page(s) 22456-7)

Point for the ¼ sec. cor. of secs. 2 & 11, at proportionate;
there is no remaining evidence of the original cor.
Set a stainless steel post, 28" long, 2½" dia., 20" in the
ground, with brass cap mkd. T26S R5W

¼ S 2
 S 11
2004

from which

 An oak, 12" dia., bears S.19¾°W., 38.0 ft. mkd. ¼ S11 BT
 A double trunk oak, 15" dia., bears N.73¾°W., 57.1 ft.,
 mkd. ¼ S2 BT.

From this cor., a point established as the 1/4 sec. cor. of
secs. 2 & 11, by George R. Lecklider, Registered Professional
Engineer No. 4079, in 1961, recorded in the Douglas County
Surveyors Office, Map File No. M21-29, bears S.0°51'36"E.,
25.55 ft., monumented with a "T" shaped iron rod, 1" dia.,
firmly set, projecting 4" above the ground. This point was
established using improper procedure and is not utilized in
the course of this survey, from which BTs mkd. by Lecklider,

continued next page

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An oak, 13" dia., bears S.47¼°E., 32.4 ft., with a healed double blaze.

An oak, 12" dia., bears S.87°W., 26.0 ft., with a healed double blaze.

This point is located 12.0 ft. W. of a woven wire fence, with fences extending north and south, and is also located 55.0 ft. N. of a graveled road, 15 ft. wide, which bears S.45°E. and N.45°W.