

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853  
-----

Set ¼ Sec. post, from which  
    A Y.oak 14" dia. bears S.54°E., 63 lks.  
    A W.Oak 12" dia. bears S.72°W., 60 lks.

Milo E. Godfrey - Deputy Co. Surveyor - Wm. Stoffel; Mike Stone - Feb. & March 1964 - C.S. File 49/125-70  
-----

Found - 20" B.Oak S.54°E., 41.6 ft. opened & found good scribing visible "BT", tree now dead but standing.

16" W.Oak S.72°W., 39.6 ft. opened & found good scribing, "BT". Tree nearly dead.

Set - Brass cap at cor. mkd. County Surveyors Office, 1964 T26S R5W ¼ S35|S36

New BTs - 17" D.Fir N.28½°E., 54.6 ft. mkd. ¼ S36 CS BT.

17" I.Cedar S.5°W., 147.2 ft. mkd. ¼ S35 CS BT.

Bearings given not true bearings, read with staff compass set on variation of 19°30'E.

Found - 1" Iron pipe 1.4 ft. north of brass cap.

Fence corner, fences south & west bears N.85°W., 4.0 ft.

Found OK by K. DeGroot, June 2000 - M132-38