

TOWNSHIP 26 RANGE 05 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set ¼ Sec. post (in ravine S.E.), from which  
    A W.Oak 12" dia. bears S.40°E., 10 lks.  
    A W.Oak 14" dia. bears S.65°W., 19 lks.

James W. Byron, Deputy; Milo Godfrey; S.A. Bilow  
December, 1958 - C.S. File 49/128-11

-----  
Found - Orig. 12" now 18" W.Oak S.40°E., 6.6 ft., I open  
          & find good scribing "¼S".  
          Orig. 14" now 24" W.Oak S.65°W., 12.5 ft., shows  
          scar. I do not open.

Note - Corner is in ravine. I SET witness corner 10 ft. North  
of True ¼ Section Corner.

Set - Brass cap at Witness Corner mkd.: Wit. Corn. 10 ft.  
      South to ¼ S23|S24 T26S R5W County Surveyor's  
      Office, 1958.

New BTs - 7" W.Oak bears N.60°E., 38.8 ft. scribed ¼ S24 W.C.  
          CS BT.  
          24" W.Oak which is also orig. S.W. BT. fo ¼ Cor.,  
          S.36°W., 19.8 ft. scribed WC ¼ S23 CS BT.

DCS0 - FD BC & both BTs in good condition - 2/6/1964 - C.S.  
49/125-30